

Panel PC Product Matrix

AR-M9522 / AR-M9552 / AR-M9572



Model No.	AR-M9522	AR-M9552	AR-M9572
System			
CPU	Intel ULV Celeron M 1GHz		
Chipset	Intel 852GM + ICH4		
Memory Type	1 x 200-pin SO-DIMM socket support 200/266MHz DDR SDRAM up to 1GB		
Memory Pre-Installed	512MB		
LCD			
Panel Size	12.1" SVGA	15" XGA	17" SXGA
Max. Resolution	800 x 600	1024 x 768	1280 x 1024
Luminance (cd/m ²)	400	450	300
Backlight Lifetime	50,000hrs		
Touch Screen Type	Analog Resistive		
Storage			
HDD	1 x 2.5" IDE HDD, 40GB		
CF	1 x Internal CF slot		
Optical Drive	1 x Slim CD-ROM/DVD Combo		
I/O			
Video Interface	1 x VGA		
Ethernet	1 x 10/100Mbps RJ45 with LED		
USB	2 x USB2.0		
Serial Port	3 x COM port		
Keyboard/Mouse	1 x PS/2 Keyboard, 1 x PS/2 Mouse		
Audio	1 x Audio Mic, Line-in, Line-out		
Parallel Port	1 x Parallel Port		
Expansion	2 x PCI slot		
Power Requirement			
Power Input	DC 11~28V		
Software			
OS Support	Windows XP, XP Embedded		
Mechanical & Environment			
Thermal Design	Fanless		
Chassis Material	Heavy-duty steel		
Dimension (W x H x D)	390mm x 264mm x 102mm	410mm x 310mm x 106mm	457mm x 355mm x 114mm
Net Weight	7.93kg	10.27kg	12kg
IR Rating	NEMA 4 / IP65 compliant front panel		
Mounting	Panel mount		
Operating Temp.	0~50°C (32~122°F)		
Storage Temp.	-10~75°C (14~167°F)		
Relative Humidity	5 to 90% @ 40°C, non-condensing		
Safety	CE, FCC class A		