AR-P170FLDC-T72

Panel PC with Intel Core 2 Duo T7250 2.0GHz, 17" Panel, 1GB RAM, Touch Screen, 2 x GbE, 4 x USB2.0, 3 x COM



- Intel Core 2 Duo T7250 2.0GHz
- 2 x 240-pin DIMM up to 4GB
- 17" Panel with Resistive Touch
- 2 x GbE, 3 x COM, 4 x USB2.0










C E F©


Panel PC




System	
CPU	Intel Core 2 Duo T7250 2.0GHz
Chipset	Intel GME965 + ICH8M
Memory Type	2 x 240-pin DIMM socket support 533/667 MHz
	DDR2 SDRAM up to 4GB
Memory Pre-Installed	1GB
LCD	
Panel Size	17"
Max. Resolution	1280 x 1024
Luminance (cd/m2)	300
Backlight Lifetime	50,000hrs
Touch Screen Type	Analog Resistive
Storage	
HDD	1 x 2.5" SATA HDD Bay
CF	1 x Internal CF slot
Optical Drive	N/A
I/O	
Video Interface	1 x VGA
Ethernet	2 x Gbps RJ45 with LED
USB	4 x USB2.0
Serial Port	3 x RS-232 (DB9)
Keyboard/Mouse	1 x PS/2 Keyboard, 1 x PS/2 Mouse
Audio	1 x MIC, 1 x Line-out
Parallel Port	N/A
Expansion	1 x PCI slot
Power Requiremen	nt
Power Input	DC 11~32V
Power Requiremen	nt
OS Support	Windows XP, XP Embedded
Mechanical & Envi	ronment
Thermal Design	Fanless
Chassis Material	Heavy-duty steel
Dimension (W x H x D)	439mm x 348mm x 93.3mm
Net Weight	12.8 kg
IR Rating	NEMA 4 / IP65 compliant front panel
Mounting	Panel / VESA75 mount
Operating Temp.	0~50°C (32~122°F)
Storage Temp.	-20~60°C (-4~140°F)
Relative Humidity	10 to 90% @ 40°C, non-condensing

Dimensions







CE, FCC class A

Safety